

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Super Diesel Additive

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

Danger

H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours. P273-Avoid release to the environment.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P314-Get medical advice / attention if you feel unwell. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	---
content %	60-80
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304
2-ethylhexyl nitrate	
Registration number (REACH)	01-2119539586-27-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	248-363-6
CAS	27247-96-7
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH044 EUH066 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Page 3 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 31.07.2023 / 0038
Replacing version dated / version: 30.08.2022 / 0037
Valid from: 31.07.2023
PDF print date: 31.07.2023
Super Diesel Additive

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here. The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
drying of the skin.
reddening of the skin
nausea
vomiting

Danger of aspiration.
oedema of the lungs
Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2
Extinction powder
Foam
Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Hydrocarbons
Toxic gases
Danger of explosion.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.

Page 4 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 31.07.2023 / 0038
Replacing version dated / version: 30.08.2022 / 0037
Valid from: 31.07.2023
PDF print date: 31.07.2023
Super Diesel Additive

Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Avoid contact with eyes or skin.
Do not carry cleaning cloths soaked in product in trouser pockets.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Under all circumstances prevent penetration into the soil.
Do not store with flammable or self-igniting materials.
Protect from direct sunlight and warming.
Store in a well ventilated place.
Store cool.

7.3 Specific end use(s)

No information available at present.
Observe the instructions for good working practice and the recommendations for risk assessment.
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

GB

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

2-ethylhexyl nitrate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,8	µg/l	
	Environment - marine		PNEC	0,08	µg/l	
	Environment - soil		PNEC	0,00019 1	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,00074	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00074	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm ²	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m ³	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,044	mg/cm ²	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Page 6 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 31.07.2023 / 0038
Replacing version dated / version: 30.08.2022 / 0037
Valid from: 31.07.2023
PDF print date: 31.07.2023
Super Diesel Additive

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:
Chemical resistant protective gloves (EN ISO 374).
If applicable
Protective nitrile gloves (EN ISO 374).
Protective Neoprene® / polychloroprene gloves (EN ISO 374).
Protective Viton® / fluoroelastomer gloves (EN ISO 374).
Minimum layer thickness in mm:
0,5
Permeation time (penetration time) in minutes:
480
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.
Protective hand cream recommended.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Gas mask filter A (EN 14387), code colour brown
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Clear
Colour:	Light brown
Odour:	Characteristic

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	145 °C
Flammability:	Flammable
Lower explosion limit:	0,7 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Upper explosion limit:	6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Flash point:	63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<7 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	5,5-7,2 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Partition coefficient n-octanol/water (log value):	3,7-5,2
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,842 g/ml (15°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives: There is no information available on this parameter.
 Oxidising liquids: There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

Risk of explosion if heated under confinement.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Super Diesel Additive						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.

GB

Page 8 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizing, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation

2-ethylhexyl nitrate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:						Experiences on persons., Harmful
Acute toxicity, by inhalation:	LCLo	>4,6	mg/l/1h	Rat		Mist
Acute toxicity, by inhalation:						Experiences on persons., Harmful
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.

Page 10 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		10-2500				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymena pyriformis		
Water solubility:							Product floats on the water surface.

2-ethylhexyl nitrate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,83	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>2,53	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:	DOC	28d	0	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not biodegradable

Page 11 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

12.3. Bioaccumulative potential:	Log Pow		5,24			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	High
12.3. Bioaccumulative potential:	BCF		1332				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 07 03 other fuels (including mixtures)

Recommendation:

Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Implement substance recycling.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 3082
 14.2. UN proper shipping name:
 UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE)
 14.3. Transport hazard class(es): 9
 14.4. Packing group: III
 14.5. Environmental hazards: environmentally hazardous
 Tunnel restriction code: -
 Classification code: M6
 LQ: 5 L
 Transport category: 3



Transport by sea (IMDG-code)

14.1. UN number or ID number: 3082
 14.2. UN proper shipping name:
 UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE)
 14.3. Transport hazard class(es): 9
 14.4. Packing group: III
 14.5. Environmental hazards: environmentally hazardous



Page 12 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 31.07.2023 / 0038
 Replacing version dated / version: 30.08.2022 / 0037
 Valid from: 31.07.2023
 PDF print date: 31.07.2023
 Super Diesel Additive

Marine Pollutant: Yes
 EmS: F-A, S-F

Transport by air (IATA)

14.1. UN number or ID number: 3082
 14.2. UN proper shipping name:
 UN 3082 Environmentally hazardous substance, liquid, n.o.s. (2-ETHYLHEXYL NITRATE)
 14.3. Transport hazard class(es): 9
 14.4. Packing group: III
 14.5. Environmental hazards: environmentally hazardous



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freight as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 95 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 4, 6, 7, 8, 10, 11, 12, 13, 14, 15, 16
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 31.07.2023 / 0038
Replacing version dated / version: 30.08.2022 / 0037
Valid from: 31.07.2023
PDF print date: 31.07.2023
Super Diesel Additive

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH044 Risk of explosion if heated under confinement.

Asp. Tox. — Aspiration hazard
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Acute Tox. — Acute toxicity - oral
Acute Tox. — Acute toxicity - dermal
Acute Tox. — Acute toxicity - inhalation
Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EBLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community

Page 14 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 31.07.2023 / 0038
Replacing version dated / version: 30.08.2022 / 0037
Valid from: 31.07.2023
PDF print date: 31.07.2023
Super Diesel Additive

EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, E_pCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Page 15 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 31.07.2023 / 0038
Replacing version dated / version: 30.08.2022 / 0037
Valid from: 31.07.2023
PDF print date: 31.07.2023
Super Diesel Additive
