

## Granville Silicone Grease

70g Tube

### PRODUCT DESCRIPTION

Granville Silicone Grease is compounded from dimethyl polysiloxane fluid, the product has a broad temperature range and is chemically inert, being resistant to water (hot, cold, steam & brine), lubricating oils, most hydrocarbons & solvents, natural gas, refinery gases and many acidic solutions.

### PRODUCT USAGE

Granville Silicone Grease has been designed for the lubrication of cylinder slides, taps, valves & stopcocks (where the presence of chemicals & solvents mean that conventional products can not be used). The product is suitable for use as a damping compound - both under conditions of high pressure and elevated temperature. Excellent dielectric properties of the grease means the product can be used with high voltage electrical systems for lubricating non-conducting contacts, prevents corona discharge and for preventing flashover on high voltage anodes.

### STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

### SHELF LIFE

3 years from date of manufacture.

### SPECIFICATION INFORMATION

Operating temperature: -40°C to +200°C  
NLGI classification: 2  
Dielectric strength: 20Kv/mm (approx)

<b>Appearance</b>	: Smooth white semi-translucent gel
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
70g Tube	0073	5020618000730



# Granville Silicone Grease

70g Tube

## **SAFETY PRECAUTIONS**

Please see our latest EC Safety Data Sheets for details.

## **TRANSPORT CLASSIFICATION**

Please see our latest EC Safety Data Sheets for details.

