

# Granville FS-ST 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Granville FS-ST 5W/30 is a fully Synthetic engine oil specially formulated for certain Stellantis group DV5R & EB2 engine types. The product helps prevent occurrences of LSPI ( Low Speed Pre-Ignition) whilst offering excellent engine protection and emission control.

Please check which oil is recommended for the engine type prior to use.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3

GM: dexos 2<sup>®</sup>

MB: 229.31, 229.51 & 229.52

PSA: B71 2290 (<2017)

API: SN & SN Plus

Stellantis: 9.55535/03

## PRODUCT BENEFITS

- \* Excellent Engine Protection
- \* Reduces occurrences of LSPI
- \* Outstanding emission Control

## PRODUCT USAGE

Use as per engine manufacturers recommendations

## DIRECTIONS FOR USE

As per the vehicle handbook



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1204	5020618012047
5 Litre	1205	5020618012054
20 Litre	1206	5020618012061
199 Litre	1207	5020618012078



# Granville FS-ST 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

## SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	:	Amber liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Insoluble in water
<b>Percentage of Biodiesel</b>	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	12.5	12.2
Density	ASTM D792	@ 15°C			0.851
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7		
Pour Point	ASTM D97	°C	-27		
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

