

## Pro-Line Maintenance Spray, white

### Description

White, adherent, water-resistant high-performance lubricant. After the solvent evaporates, leaves behind a soft lubricant whose excellent stability in low and high temperatures allows it to be used in the toughest conditions. Protects all components ideally through reliable corrosion protection and good resistance to water. Is particularly clean when applied thanks to the extremely adherent lubricating film. Lubricates and maintains all components.

### Properties

- excellent high-pressure and wear protection properties
- good corrosion protection
- outstanding bond strength
- good water resistance
- clean application
- prevents friction corrosion
- outstanding lubricating action
- also suitable for overhead work
- excellent high and low temperature behavior
- silicone-free

### Technical data

Color / appearance	white
Base	Mineralöl, Festschmierstoffe
Thickener	Bentonit
Density	ca. 1,0 g/cm <sup>3</sup>
ISO 2176	NLGI 2
Consistency modifiers	without
Operating temperature range	-30 to +250 °C
Propellant	propane, butane
Odor	characteristic
Form	liquid, aerosol
Density at 20 °C	0,64 g/ml

### Areas of application

For lubricating moving parts such as shafts, hinges, joints, pins, Bowden cables, slide rails, chains, springs, lock strikers, all fine mechanisms, spindles, guides, springs, etc.

### Application

Surfaces to be treated must be clean and free from dirt and moisture. Shake well before use. Depending on application, spray on a coating of the desired thickness. The fold-out capillary tube ensures precision spraying. With the capillary tube folded in, large areas are sprayed. Spray large areas without the capillary tube from about 20-25 cm. Also sprays when

inverted.

### Available pack sizes

400 ml Can aerosol	7387
	D-GB-I-E-P
400 ml Can aerosol	9914
	GB-DK-FIN-N-S

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

